

UNIRAIL HT – EN 50382-2 3600 V 150°C - type F

UNIKA (Italy) - EN 50382-2 3600 V 10 F 150°C - code

TECHNICAL DATA

Temperature rating up to and including 150°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, acids and alkali

Enhanced abrasion and tear resistance and enhanced thermal aging for long term (beyond 20000h at 170°C) according to the TRENITALIA specification and principal OEMs requests

Bending radius: fixed ≥ 3 outer diameter, flexible ≥ 5 outer diameter

Range of approval:

According to table 3 (cross-section $2,5 \div 400 \text{ mm}^2$) of EN 50382-2 for cables rated 3600V (see IMQ test certificate)

Item n°	Cross-section [mm ²]	Diameter without braid [mm]	Cable mass [kg/km]
RA901	2,5	7,6 ÷ 8,9	84
RA902	4	8,1 ÷ 9,5	102
RA903	6	9,0 ÷ 10,6	124
RA904	10	9,5 ÷ 11,1	170
RA905	16	10,5 ÷ 12,3	241
RA906	25	11,8 ÷ 13,8	329
RA907	35	13,0 ÷ 15,2	422
RA908	50	14,4 ÷ 16,9	571
RA909	70	16,1 ÷ 18,9	760
RA910	95	17,5 ÷ 20,5	984
RA911	120	19,3 ÷ 22,6	1216
RA912	150	20,8 ÷ 24,4	1474
RA913	185	22,6 ÷ 26,5	1810
RA914	240	25,4 ÷ 29,8	2326
RA915	300	27,7 ÷ 32,4	2780
RA916	400	30,8 ÷ 36,0	3610

CONSTRUCTION

Type: single core unsheathed cable

Conductor: tinned copper conductor according to class 5 EN 60228

Screening separator: semiconductive black tape

Insulation: silicon rubber compound, type EI111 according to Standard EN 50382-1, colour black if not otherwise stated

Textile braid: available upon request

Marking: UNIKA (Italy) – EN 50382-2 3600V cross-section F 150°C – WW/YYYY - traceability code

Fire safety: hazard level HL3

according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.