


UNIRAIL S – EN 50264-3-2 300 V – type MMS

UNIKA (Italy) – EN 50264-3-2 300 V 4x2,5 MMS eode



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, fuels, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table 2 (cross-section 1 ÷ 2,5 mm²) of EN 50264-3-2 for cables rated 300V (see IMQ test certificate)

Item n°	Cross-section [mm ²]	Diameter [mm]	Cable mass [kg/km]
RB501	2x1	6,0 ÷ 7,1	60
RB525	3x1	6,5 ÷ 7,5	86
RB502	4x1	7,0 ÷ 8,2	94
RB530	6x1	8,1 ÷ 8,9	168
RB503	7x1	8,2 ÷ 9,6	137
RB526	8x1	9,4 ÷ 10,6	185
RB504	9x1	10,2 ÷ 11,9	195
RB505	12x1	10,9 ÷ 12,7	238
RB506	19x1	13,2 ÷ 15,4	368
RB507	24x1	15,2 ÷ 17,8	461
RB508	32x1	16,6 ÷ 19,4	578
RB509	37x1	17,2 ÷ 20,1	642
RB510	40x1	18,2 ÷ 21,3	710
RB511	4x1,5	8,0 ÷ 9,4	119
RB512	7x1,5	9,6 ÷ 11,3	199
RB527	8x1,5	10,4 ÷ 12,4	245

Item n°	Cross-section [mm ²]	Diameter [mm]	Cable mass [kg/km]
RB513	9x1,5	12,1 ÷ 14,2	260
RB532	10x1,5	13,1 ÷ 13,9	323
RB514	12x1,5	13,0 ÷ 15,2	324
RB515	19x1,5	15,3 ÷ 17,9	498
RB516	24x1,5	18,1 ÷ 21,2	620
RB517	32x1,5	19,8 ÷ 23,2	803
RB518	37x1,5	20,5 ÷ 24,0	891
RB531	2x2,5	8,3 ÷ 9,1	133
RB519	4x2,5	9,2 ÷ 10,8	180
RB520	7x2,5	11,1 ÷ 13,0	285
RB521	9x2,5	13,9 ÷ 16,3	393
RB522	12x2,5	15,0 ÷ 17,5	488
RB523	19x2,5	17,8 ÷ 20,8	708
RB524	24x2,5	20,6 ÷ 24,1	905
RB528	2x1,5	7,3	101
RB529	3x1,5	7,8	116

Add letter **G** after the item number for cables with yellow/green conductor

CONSTRUCTION

Type: multicore screened cable

Conductor: tinned copper conductor according to class 5 EN 60228

Tape (optional): coloured tape

Insulation: crosslinked compound, type EI109 according to Standard EN 50264-1, colour black with numbers with or without yellow-green if not otherwise stated (upon request compound type EI110)

Tape: non-hygroscopic tape on the assembly

Screen: tinned copper wire braid with optional non-hygroscopic tape

Sheath: crosslinked compound, type EM104 according to Standard EN 50264-1, colour black if not otherwise stated

Marking: UNIKA (Italy) – EN 50264-3-2 300V (core number x cross-section) MMS – WW/YYYY - traceability code

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.

Unless otherwise specified, all values are nominal, other values can be provided on request. The images are made for the sole purpose of illustrating the product and are purely indicative.