


UNIRAIL HT – EN 50382-2 3600 V 150°C - type FFS

UNIKA (Italy) - EN 50382-2 3600 V 50 FFS 150°C - code



TECHNICAL DATA

Temperature rating up to and including 150°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, acids and alkali

Enhanced abrasion and tear resistance and enhanced thermal aging for long term (beyond 20000h at 170°C) according to the TRENITALIA specification and principal OEMs requests

Bending radius: fixed ≥ 3 outer diameter, flexible ≥ 5 outer diameter

Range of approval:

In compliance with table 5 (cross-section $2,5 \div 400 \text{ mm}^2$) of EN 50382-2 for cables rated 3600V (see IMQ test certificate)

Item n°	Cross-section [mm ²]	Diameter [mm]	Cable mass [kg/km]
RAC05	16	12,8 ÷ 15,0	370
RAC06	25	14,7 ÷ 17,2	485
RAC07	35	15,9 ÷ 18,6	580
RAC08	50	17,5 ÷ 20,5	750
RAC09	70	19,2 ÷ 22,4	1010
RAC10	95	20,8 ÷ 24,3	1200
RAC11	120	22,4 ÷ 26,2	1485
RAC11H	120	26,5 ÷ 30,0	1620
RAC12	150	24,1 ÷ 28,2	1770
RAC13	185	26,4 ÷ 30,9	2160
RAC14	240	29,4 ÷ 34,4	2720

CONSTRUCTION

Type: single core screened cable with EMC performance

Conductor: tinned copper conductor according to class 5 EN 60228

Screening separator: semiconductive black tape

Insulation: silicon rubber compound, type EI111 according to Standard EN 50382-1, colour white if not otherwise stated

Tape (optional): polyester or other non-hygroscopic tape

Screen: tinned copper wire braid with optional non-hygroscopic tape, minimum coverage 85%

Sheath: silicon rubber compound, type EM107 according to Standard EN 50382-1, colour black if not otherwise stated

Marking: UNIKA (Italy) – EN 50382-2 3600V cross-section FFS 150°C – WW/YYYY - traceability code

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

Add letter C after the item number to have spiral tinned copper wire instead of braid

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.

Unless otherwise specified, all values are nominal, other values can be provided on request. The images are made for the sole purpose of illustrating the product and are purely indicative.