


UNIRAIL S – EN 50264-3-1 1800 V – type MM

UNIKA (Italy) - EN 50264-3-1 1800 V 70 MMS - code



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, fuels, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table 3 (cross-section 1,5 ÷ 400 mm²) of EN 50264-3-1 for cables rated 1800V (see IMQ test certificate)

Item n°	Cross-section [mm ²]	Diameter [mm]	Cable mass [kg/km]
RB201	1,5	5,7 ÷ 6,7	49
RB202	2,5	6,0 ÷ 7,0	61
RB203	4	6,5 ÷ 7,6	78
RB204	6	7,0 ÷ 8,1	100
RB205	10	8,2 ÷ 9,6	156
RB206	16	9,2 ÷ 10,8	215
RB207	25	11,5 ÷ 13,4	343
RB208	35	12,7 ÷ 14,9	436
RB209	50	14,1 ÷ 16,5	591
RB210	70	15,8 ÷ 18,5	781
RB211	95	18,0 ÷ 21,0	1045
RB212	120	19,6 ÷ 22,9	1278
RB213	150	21,4 ÷ 25,1	1564
RB214	185	23,4 ÷ 27,4	1923
RB215	240	25,9 ÷ 30,3	2434
RB216	300	28,1 ÷ 32,9	2940
RB217	400	32,0 ÷ 37,4	3980

CONSTRUCTION

Type: single core sheathed cable

Conductor: tinned copper conductor according to class 5 EN 60228

Tape (optional): coloured tape for cross-section ≥ 16 mm²

Insulation: crosslinked compound, type EI109 according to Standard EN 50264-1, colour black if not otherwise stated (upon request compound type EI110)

Tape (optional): or talcum powder for strippability

Sheath: crosslinked compound, type EM104 according to Standard EN 50264-1, colour black if not otherwise stated

Marking: UNIKA (Italy) – EN 50264-3-1 1800V cross-section MM – WW/YYYY - traceability code

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.