UNIKA - ROLLING STOCK CABLES - UNIRAIL S – EN 50264-3-1 1800 V – type MMS

UNIRAIL S - EN 50264-3-1 1800 V - type MMS

UNIKA (Italy) - EN 50264-3-1 1800 V 70 MMS - code



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, fuels, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

In compliance with EN 50264-3-1 for cables rated 1800V (see IMQ test certificate)

Item n°	Cross-section [mm²]	Diameter [mm]	Cable mass [kg/km]
RCA07	25	13,0 ÷ 15,2	440
RCA08	35	14,5 ÷ 16,7	550
RCA09	50	15,3 ÷ 17,5	675
RCA10	70	17,0 ÷ 19,2	910
RCA11	95	19,2 ÷ 22,0	1180

CONSTRUCTION

Type: single core sheathed cable

Conductor: tinned copper conductor according to class 5 EN 60228

Tape (optional): coloured tape for cross-section ≥ 16 mm²

Insulation: crosslinked compound, type El109 according to Standard EN 50264-1, colour black if not otherwise stated (upon request compound type El110)

Tape: non-hygroscopic tape on the assembly

Screen: tinned copper wire braid with optional non-hygroscopic tape

Sheath: crosslinked compound, type EM104 according to Standard EN 50264-1, colour black if not otherwise stated

Marking: UNIKA (Italy) – EN 50264-3-1 1800V cross-section MMS – WW/YYYY traceability code

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.