

UNIRAIL S – EN 50264-3-1 3600 V - type MM

UNIKA (Italy) - EN 50264-3-1 3600 V 95 MM - code

TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, fuels, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table 4 (cross-section 2,5 ÷ 400 mm²) of EN 50264-3-1 for cables rated 3600V (see IMQ test certificate)

Item n°	Cross-section [mm ²]	Diameter [mm]	Cable mass [kg/km]
RB301	2,5	8,6 ÷ 10,1	113
RB302	4	9,1 ÷ 10,7	134
RB303	6	9,6 ÷ 11,2	158
RB304	10	10,4 ÷ 12,2	210
RB305	16	11,5 ÷ 13,4	272
RB306	25	13,7 ÷ 16,1	416
RB307	35	14,9 ÷ 17,5	517
RB308	50	16,4 ÷ 19,1	680
RB309	70	18,0 ÷ 21,1	880
RB310	95	19,5 ÷ 22,8	1120
RB311	120	21,4 ÷ 25,1	1376
RB312	150	22,9 ÷ 26,8	1646
RB313	185	25,1 ÷ 29,4	2034
RB314	240	28,3 ÷ 33,1	2608
RB315	300	30,6 ÷ 35,8	3128
RB316	400	33,7 ÷ 39,4	4205

CONSTRUCTION

Type: single core sheathed cable

Conductor: tinned copper conductor according to class 5 EN 60228

Tape: semiconductive tape to reduce partial discharge effect

Insulation: crosslinked compound, type EI109 according to Standard EN 50264-1, colour black if not otherwise stated (upon request compound type EI110)

Tape (optional): or talcum powder for strippability

Sheath: crosslinked compound, type EM104 according to Standard EN 50264-1, colour black if not otherwise stated

Marking: UNIKA (Italy) – EN 50264-3-1 3600V cross-section MM – WW/YYYY - traceability code

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.