


UNIRAIL S – EN 50264-3-1 3600 V - type MMS

UNIKA (Italy) - EN 50264-3-1 3600 V 95 MMS - code



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, fuels, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table 4 (cross-section 2,5 ÷ 400 mm²) of EN 50264-3-1 for cables rated 3600V (see IMQ test certificate)

Item n°	Cross-section [mm ²]	Diameter [mm]	Cable mass [kg/km]
RC906	25	14,8 ÷ 16,5	510
RC907	35	16,1 ÷ 18,0	615
RC908	50	17,5 ÷ 19,5	770
RC909	70	19,1 ÷ 21,5	1030
RC910	95	21,1 ÷ 23,5	1210
RC911	120	23,0 ÷ 25,5	1550
RC912	150	25,0 ÷ 28,0	1840
RC913	185	27,0 ÷ 30,0	2260
RC914	240	30,5 ÷ 33,5	2850

CONSTRUCTION

Type: single core sheathed cable

Conductor: tinned copper conductor according to class 5 EN 60228

Tape: semiconductive tape to reduce partial discharge effect

Insulation: crosslinked compound, type EI109 according to Standard EN 50264-1, colour black if not otherwise stated (upon request compound type EI110)

Tape (optional): or talcum powder for strippability

Sheath: crosslinked compound, type EM104 according to Standard EN 50264-1, colour black if not otherwise stated

Marking: UNIKA (Italy) – EN 50264-3-1 3600V cross-section MMS – WW/YYYY - traceability code

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.

Unless otherwise specified, all values are nominal, other values can be provided on request.
The images are made for the sole purpose of illustrating the product and are purely indicative.