

UNIRAIL S – EN 50264-3-2 300 V – type MM – EN 50200

UNIKA (Italy) – EN 50264-3-2 300 V MM - EN 50200 PH120 - code



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, fuels, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table 1 of EN 50264-3-2 for cables rated 600V (see IMQ test certificate) with fire resisting time not below 120 min

Item n°	Cross-section [mm²]	Max. outer diameter [mm]	Cable mass [kg/km]
RB900	2x0,50	6,0	44
RB910	3x0,50	6,3	51
RB908	4x0,50	7,2	66
RB911	6x0,50	8,7	91
RB909	2x0,75	6,5	50
RB907	3x0,75	7,0	63
RB901	2x1	8,0	53
RB905	3x1	8,5	74
RB906	4x1	9,0	92
RB904	6x1	9,6	135
RB902	2x1,5	8,5	81
RB913	3x1,5	9,0	95
RB916	4x1,5	10,0	120
RB903	2x2,5	9,5	106
RB914	3x2,5	10,0	135
RB917	4x2,5	11,0	175
RB912	2x4	10,8	150
RB915	3x4	11,5	180
RB918	4x4	12,8	240

CONSTRUCTION

Type: multicore cable, fire resistant

Conductor: tinned copper conductor according to class 5 EN 60228

Tape: mica tape

Insulation: crosslinked compound, type EI109 according to Standard EN 50264-1, colour black with numbers

Tape: non-hygroscopic tape on the assembly

Sheath: crosslinked compound, type EM104 according to Standard EN 50264-1, colour red if not otherwise stated

Marking: UNIKA (Italy) – EN 50264-3-2 300V cross-section MM – EN 50200 PH120 - WW/YYYY - *traceability code*

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.