


UNIRAIL TW – EN 50306-3 300 V – type MMS

Single core and multicore cables, screened and thin wall sheathed

UNIKA (Italy) – EN 50306-3 300 V 4x1,5 MMS - code



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table TW2 of EN 50306-3 for cables rated 300V (see IMQ test certificate)

CONSTRUCTION

Conductor: tinned copper conductor according to table TW1

Insulation: double layer of special compound

Identification: numbered white cores (other identification methods may be agreed)

Laying-up: cores are twisted together in multicore cables with optional non-hygroscopic tape

Screen: tinned copper wire braid

Sheath: cross-linked compound type S2 according to EN 50306-1 for rated temperature 90°C, colour black

Marking: UNIKA (Italy) – EN 50306-3 300V (n°cores)x(cross-section) MMS 90 – WW/YYYY - traceability code

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

Table TW2 - Dimensional data

Item n°	Conductor n° wires x cross- section [mm²]	Diameter [mm]	Item n°	Conductor n° wires x cross- section [mm²]	Diameter [mm]
RM501	1x0,5	2,3÷2,9	RM512	4x1	5,0÷6,2
RM502	2x0,5	3,5÷4,4	RM528	6x1	6,3÷7,3
RM503	3x0,5	3,7÷4,7	RM524	7x1	6,4÷7,4
RM504	4x0,5	4,0÷5,2	RM529	8x1	7,5÷8,5
RM521	6x0,5	5,5÷6,5	RM513	1x1,5	3,1÷3,6
RM525	8x0,5	6,1÷7,1	RM514	2x1,5	5,1÷6,1
RM522	16x0,5	7,5÷8,5	RM515	3x1,5	5,4÷6,4
RM505	1x0,75	2,5÷3,1	RM516	4x1,5	6,0÷7,0
RM506	2x0,75	3,9÷4,8	RM523	5x1,5	6,6÷7,6
RM507	3x0,75	4,0÷5,2	RM530	6x1,5	7,3÷8,3
RM508	4x0,75	4,5÷5,7	RM531	8x1,5	8,5÷9,5
RM526	6x0,75	6,1÷7,1	RM517	1x2,5	3,6÷4,5
RM527	8x0,75	7,3÷8,3	RM518	2x2,5	6,4÷7,5
RM509	1x1	2,7÷3,3	RM519	3x2,5	6,8÷8,0
RM510	2x1	4,2÷5,3	RM520	4x2,5	7,5÷8,7
RM511	3x1	4,5÷5,7			

Unless otherwise specified, all values are nominal, other values can be provided on request.
The images are made for the sole purpose of illustrating the product and are purely indicative.

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.