


UNIRAIL TW – EN 50306-4 300 V – type MM (Table 1)

Multicore unscreened cables, standard wall sheathed

UNIKA (Italy) – EN 50306-4 300 V 4x1,5 MM - code



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table TW3 of EN 50306-4 for cables rated 300V (see IMQ test certificate). Further constructions are available upon request.

CONSTRUCTION

Conductor: tinned copper conductor according to table TW1

Insulation: double layer of special compound

Identification: numbered white cores (other identification methods may be agreed)

Laying-up: cores are twisted together in multicore cables with optional non-hygroscopic tape

Sheath: cross-linked compound type EM104 according to EN 50306-1, colour black

Marking: UNIKA (Italy) – EN 50306-4 300V “1n” (n°cores)x(cross-section) MM 90 – WW/YYYY - “traceability code”
n: E for exposed installations or P for protected installations

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

Table TW3 – Multicore unscreened sheathed cables - Dimensional data

Item n°	Cable type n° cores x cross-section [mm²]	Diameter exposed type [mm]	Diameter protected type [mm]	Item n°	Cable type n° cores x cross-section [mm²]	Diameter exposed type [mm]	Diameter protected type [mm]
RM235	2x0,5	4,9 ÷ 5,9	3,5÷4,5	RM214	13x1	9,7 ÷ 10,9	8,7÷10,1
RM236	3x0,5	5,1 ÷ 6,1	3,8 ÷4,8	RM215	19x1	10,7 ÷ 11,9	9,8÷11,2
RM201	4x0,5	5,5 ÷ 6,5	4,1÷5,3	RM226	20x1	10,9 ÷ 12,1	10,3 ÷ 11,5
RM202	7x0,5	6,3 ÷ 7,3	4,9÷6,1	RM216	37x1	14,0 ÷ 15,6	13,3÷14,7
RM238	9x0,5	6,8 ÷ 7,8	6,3÷6,9	RM232	2x1,5	6,3 ÷ 7,3	5,0 ÷ 6,0
RM203	13x0,5	8,3 ÷ 9,3	7,3÷8,5	RM239	3x1,5	6,6 ÷ 7,6	5,3 ÷ 6,3
RM204	19x0,5	9,0 ÷ 10,2	8,1÷9,3	RM217	4x1,5	7,4 ÷ 8,4	6,0÷7,2
RM237	25x0,5	10,2 ÷ 11,4	9,6÷10,4	RM240	5x1,5	8,1 ÷ 9,3	7,0 ÷ 8,2
RM205	37x0,5	12,3 ÷ 13,5	10,8÷12,2	RM227	6x1,5	8,5 ÷ 9,7	7,6 ÷ 8,6
RM233	2x0,75	5,3 ÷ 6,3	4,0 ÷ 5,0	RM218	7x1,5	8,6 ÷ 9,8	7,7 ÷ 8,9
RM241	3x0,75	5,5 ÷ 6,5	4,2 ÷ 5,2	RM228	12x1,5	10,9 ÷ 12,1	10,3 ÷ 11,5
RM206	4x0,75	6,0 ÷ 7,0	4,6÷5,8	RM219	13x1,5	11,7 ÷ 12,9	10,7÷12,1
RM207	7x0,75	6,9 ÷ 7,9	5,5÷6,6	RM220	19x1,5	13,0 ÷ 14,2	12,0 ÷13,4
RM208	13x0,75	9,1 ÷ 10,3	8,2÷9,4	RM229	20x1,5	13,2 ÷ 14,4	12,6 ÷ 13,8
RM209	19x0,75	10,0 ÷ 11,2	9,0÷10,4	RM221	37x1,5	17,2 ÷18,8	16,2÷ 18,0
RM210	37x0,75	13,2 ÷ 14,4	12,2÷13,6	RM222	2x2,5	7,7 ÷ 8,7	6,7÷7,9
RM211	48x0,75	14,8 ÷ 16,4	13,9÷15,7	RM223	3x2,5	8,1 ÷ 9,1	7,1÷ 8,3
RM225	2x1	5,6 ÷ 6,6	4,3 ÷ 5,3	RM224	4x2,5	8,8 ÷ 10,0	7,9 ÷ 9,1
RM242	3x1	5,9 ÷ 6,9	4,6 ÷ 5,6	RM234	6x2,5	10,0 ÷ 11,2	9,5 ÷ 10,3
RM212	4x1	6,3 ÷ 7,3	4,9÷6,1	RM230	12x2,5	13,0 ÷ 14,2	12,5 ÷ 13,7
RM213	7x1	7,3 ÷ 8,3	6,0÷7,0	RM231	20x2,5	16,0 ÷ 17,2	15,6 ÷ 16,8

Add letter **E** for exposed installations or **P** for protected installations at the end of the item number

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.

Unless otherwise specified, all values are nominal, other values can be provided on request. The images are made for the sole purpose of illustrating the product and are purely indicative.