

UNIRAIL TW – EN 50306-4 300 V – type MMS (Table 5)

Multipair cables, individually screened and sheathed and with an overall sheath

UNIKA (Italy) – EN 50306-4 300 V 2x2x0,75 MMS - code



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table TW4 of EN 50306-4 for cables rated 300V (see IMQ test certificate). Further constructions are available upon request.

Table TW4 – Multicore screened sheathed cables - Dimensional data

Item n°	Cable type n° cores x cross- section [mm²]	Diameter exposed type [mm]	Diameter protected type [mm]
RM401	2x2x0,5	10,1÷11,3	9,0÷10,2
RM402	3x2x0,5	10,8÷12,0	9,6÷10,8
RM403	4x2x0,5	11,8÷13,0	10,7÷12,0
RM404	7x2x0,5	13,9÷15,5	13,0÷14,2
RM405	2x2x0,75	10,9÷12,1	9,8÷11,0
RM406	3x2x0,75	11,6÷13,0	10,5÷11,7
RM407	4x2x0,75	12,8÷14,3	11,6÷12,8
RM408	7x2x0,75	15,1÷16,9	14,0÷15,6
RM417	1x2x(1)	7,0÷8,0	6,2 ÷ 7,2
RM409	2x2x1	11,3÷12,5	10,2÷11,6
RM410	3x2x1	12,0÷13,5	10,9÷12,3
RM411	4x2x1	13,2÷14,7	12,1÷13,3
RM412	7x2x1	15,7÷17,3	14,6÷16,3
RM413	2x2x1,5	13,3÷14,5	12,2÷13,4
RM414	3x2x1,5	14,0÷15,6	13,1÷14,3
RM415	4x2x1,5	15,5÷17,1	14,3÷15,9
RM416	7x2x1,5	18,7÷20,5	17,6÷19,2

Add letter **E** for exposed installations or **P** for protected installations at the end of the item number

CONSTRUCTION

Conductor: tinned copper conductor according to table TW1

Insulation: double layer of special compound

Identification: numbered white cores (other identification methods may be agreed)

Pairing: cores are twisted in pairs

Pair screen: tinned wire braid

Pair sheath: cross-linked compound, black numbered

Laying up: sheathed pairs are stranded together

Sheath: cross-linked compound type EM104 according to EN 50306-1

Marking: UNIKA (Italy) – EN 50306-4 "5n" (n°pairs)x(cross-section) MMS 90 – WW/YYYY - traceability code
n: E for exposed installations or P for protected installations

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.

Unless otherwise specified, all values are nominal, other values can be provided on request. The images are made for the sole purpose of illustrating the product and are purely indicative.