

UNIRAIL HT – EN 50382-2 1800 V 150°C - type F

UNIKA (Italy) - EN 50382-2 1800 V 16 F 150°C - code

TECHNICAL DATA

Temperature rating up to and including 150°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, acids and alkali

Enhanced abrasion and tear resistance and enhanced thermal aging for long term (beyond 20000h at 170°C) according to the TRENITALIA specification and principal OEMs requests

Bending radius: fixed ≥ 3 outer diameter, flexible ≥ 5 outer diameter

Range of approval:

According to table 1 (cross-section 1,5 ÷ 400 mm²) of EN 50382-2 for cables rated 1800V (see IMQ test certificate)

Item n°	Cross-section [mm ²]	Diameter without braid [mm]	Cable mass [kg/km]
RA801	1,5	6,3 ÷ 7,3	57
RA802	2,5	6,7 ÷ 7,8	69
RA803	4	7,2 ÷ 8,4	86
RA804	6	7,7 ÷ 9,0	107
RA805	10	8,5 ÷ 10,0	151
RA806	16	9,6 ÷ 11,2	219
RA807	25	10,9 ÷ 12,7	305
RA808	35	12,1 ÷ 14,1	394
RA809	50	13,5 ÷ 15,8	540
RA810	70	15,2 ÷ 17,8	725
RA811	95	17,0 ÷ 19,9	961
RA812	120	18,6 ÷ 21,7	1182
RA813	150	20,1 ÷ 23,5	1438
RA814	185	21,7 ÷ 25,4	1760
RA815	240	24,1 ÷ 28,2	2249
RA816	300	26,4 ÷ 30,9	2680
RA817	400	29,9 ÷ 34,9	3450

CONSTRUCTION

Type: single core unsheathed cable

Conductor: tinned copper conductor according to class 5 EN 60228

Screening separator: semiconductive black tape

Insulation: silicon rubber compound, type EI111 according to Standard EN 50382-1, colour black if not otherwise stated

Textile braid: available upon request

Marking: UNIKA (Italy) – EN 50382-2 1800V cross-section F 150°C – WW/YYYY - traceability code

Fire safety: hazard level HL3

according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.

Unless otherwise specified, all values are nominal, other values can be provided on request. The images are made for the sole purpose of illustrating the product and are purely indicative.