


UNIRAIL HT – EN 50382-2 1800 V 150°C - type FF

UNIKA (Italy) - EN 50382-2 1800 V 25 FF 150°C - code



TECHNICAL DATA

Temperature rating up to and including 150°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, acids and alkali

Enhanced abrasion and tear resistance and enhanced thermal aging for long term (beyond 20000h at 170°C) according to the TRENITALIA specification and principal OEMs requests

Bending radius: fixed ≥ 3 outer diameter, flexible ≥ 5 outer diameter

Range of approval:

According to table 2 (cross-section 1,5 ÷ 400 mm²) of EN 50382-2 for cables rated 1800V (see IMQ test certificate)

Item n°	Cross-section [mm ²]	Diameter [mm]	Cable mass [kg/km]
RAA01	1,5	6,8 ÷ 7,9	63
RAA02	2,5	7,2 ÷ 8,4	76
RAA03	4	7,7 ÷ 9,0	93
RAA04	6	8,2 ÷ 9,6	115
RAA05	10	9,4 ÷ 11,0	168
RAA06	16	10,5 ÷ 12,2	236
RAA07	25	12,3 ÷ 14,4	339
RAA08	35	13,6 ÷ 15,9	432
RAA09	50	15,0 ÷ 17,5	583
RAA10	70	16,8 ÷ 19,7	780
RAA11	95	19,0 ÷ 22,2	1039
RAA12	120	20,8 ÷ 24,3	1276
RAA13	150	22,3 ÷ 26,1	1539
RAA14	185	24,5 ÷ 28,6	1871
RAA15	240	27,1 ÷ 31,7	2417
RAA16	300	29,5 ÷ 34,6	2760
RAA17	400	33,2 ÷ 38,9	3620

CONSTRUCTION

Type: single core sheathed cable

Conductor: tinned copper conductor according to class 5 EN 60228

Screening separator: semiconductive black tape

Insulation: silicon rubber compound, type EI111 according to Standard EN 50382-1, colour white if not otherwise stated

Tape (optional): polyester or other non-hygroscopic tape

Sheath: silicon rubber compound, type EM107 according to Standard EN 50382-1, colour black if not otherwise stated

Marking: UNIKA (Italy) – EN 50382-2 1800V cross-section FF 150°C – WW/YYYY - traceability code

Fire safety: hazard level HL3 according to Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.