

Single and multicore, halogen-free, fire resistant, power cables for outdoor installations according to RFI specifications

Item n°	Cross-section [mm²]	Maximum diameter [mm]	RFI item
R0301	1x1,5	6,4	803/200
R0302	1x2,5	7,0	803/201
R0303	1x4	7,4	803/202
R0304	1x6	9,0	803/203
R0305	1x10	10,0	803/204
R0306	1x16	10,5	803/205
R0307	1x25	12,5	803/206
R0308	1x35	14,0	803/207
R0309	1x50	16,0	803/208
R0310	2x1,5	12,0	803/209
R0311	2x2,5	13,0	803/210
R0312	2x4	14,0	803/211
R0313	2x6	16,0	803/212
R0314	2x10	18,5	803/213
R0315	2x16	19,5	803/214
R0316	2x25	23,5	803/215
R0317	3x1,5	13,0	803/216
R0318	3x2,5	14,0	803/217
R0319	3x4	15,0	803/218
R0320	3x6	17,0	803/219
R0321	3x10	20,0	803/220
R0322	3x16	21,5	803/221
R0323	3x25	25,0	803/222
R0324	4x1,5	14,0	803/223
R0325	4x2,5	15,0	803/224
R0326	4x4	16,5	803/225
R0327	4x6	19,0	803/226
R0328	4x10	22,0	803/227
R0329	4x16	23,5	803/228
R0330	4x25	27,5	803/229

CONSTRUCTION ACCORDING TO TE 653 AND CEI 20-45

Conductor: tinned copper conductor according to CEI EN 60228 class 5

Insulation: mica tape(s) and halogen free compound type G10 according to CEI 20-11

Sheath: halogen free compound type M1 according to CEI 20-11, colour blue

Marking: UNIKA(Italy) – “RFI item” – EF-SATRF – year

Rated voltage: 0,6/1 kV

Fire safety: CEI EN 60332-1-2, CEI EN 60332-3-24, CEI 20-37, EN 50200

Unless otherwise specified, all values are nominal, other values can be provided on request.
The images are made for the sole purpose of illustrating the product and are purely indicative.

The characteristics of the products, described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.