


UNIRAIL D – ETHERNET CABLE CATEGORY 5e

Type: **1x4x22 AWG/19 SF/UTP**


Code: **RW100A**



CONSTRUCTION	
Conductor	stranded tinned copper wire – 22 AWG/19 (0,35 mm ²)
Insulation	Polyolefin
Insulation colours	white ÷ blue ÷ yellow ÷ orange
Assembly of core	Stranded to quad: • pair 1 white/blue • pair 2 yellow/orange
Separation	polyester tape
Inner jacket	Halogen-free compound
Overall shield	aluminium/polyester tape + tinned copper braid 85% coverage
Outer jacket	crosslinked compound, type EM104 according to standard EN 50264-1 - green colour if not otherwise stated
Marking	UNIKA (Italy) – Profinet Cable CAT. 5e (1x4x22 AWG/19) M - 100 ohm - WW/YYYY – <i>traceability code</i>

Type: **1x4x26 AWG/7 SF/UTP**

Code: **RW100B**



CONSTRUCTION	
Conductor	stranded bare copper wire – 26 AWG/7 (0,14 mm ²)
Insulation	polyolefin
Insulation colours	white ÷ blue ÷ yellow ÷ orange
Assembly of core	Stranded to quad: • pair1 white/blue • pair2 yellow/orange
Separation	polyester tape
Overall shield	aluminium/polyester tape + tinned copper braid 85% coverage
Outer jacket	crosslinked compound, type EM104 according to standard EN 50264-1. Green colour if not otherwise stated
Marking	UNIKA (Italy) – Profinet Cable CAT. 5e (1x4x26AWG/7) M - 100 ohm - WW/YYYY – <i>traceability code</i>

Unless otherwise specified, all values are nominal, other values can be provided on request.
The images are made for the sole purpose of illustrating the product and are purely indicative.


The characteristics of the products, described in the data sheet, do not constitute any contractual binding.

UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.

TDS 00/2025


Type: **4x2x22 AWG/19 SF/UTP**
Code: **RW100C**

UNIKA




CONSTRUCTION	
Conductor	stranded tinned copper wire – 22 AWG/19 (0,35 mm ²)
Insulation	polyolefin
Insulation colours	white-blue ÷ white-orange ÷ white-brown ÷ white-green
Assembly of core	Pair stranded together : • pair1 white/blue • pair2 white/orange • pair3 white/brown • pair4 white/green
Overall shield	aluminized/ polyester tape - tinned copper braid 85% coverage
Outer jacket	crosslinked compound, type EM104 according to standard EN 50264-1. Green colour if not otherwise stated
Marking	UNIKA (Italy) – Ethernet Cable CAT. 5e (4x2x22AWG/19) M - 100 ohm - WW/ YYYY – <i>traceability code</i>

Type: **4x2x26 AWG/7 SF/UTP**
Code: **RW100D**




CONSTRUCTION	
Conductor	stranded tinned copper wire – 26 AWG/7 (0,14 mm ²)
Insulation	polyolefin
Insulation colours	white-blue ÷ white-orange ÷ white-brown ÷ white-green
Assembly of core	Pair stranded together : • pair 1 white/blue • pair 2 white/orange • pair 3 white/brown • pair 4 white/green
Overall shield	aluminized/polyester tape - tinned copper braid 85% coverage
Outer jacket	crosslinked compound, type EM104 according to standard EN 50264-1. Green colour if not otherwise stated
Marking	UNIKA (Italy) – Ethernet Cable CAT. 5e (4x2x26AWG/7) M - 100 ohm - WW/YYYY – <i>traceability code</i>

Type: **4x2x24 AWG/7 SF/UTP**
Code: **RW100E**




CONSTRUCTION	
Conductor	stranded bare copper wire – 24 AWG/7 (0,25 mm ²)
Insulation	polyolefin
Insulation colours	white-blue ÷ white-orange ÷ white-brown ÷ white-green
Assembly of core	Pair stranded together : • pair1 white/blue • pair2 white/orange • pair3 white/brown • pair4 white/green
Overall shield	aluminized/ polyester tape - tinned copper braid 85% coverage
Outer jacket	crosslinked compound, type EM104 according to standard EN 50264-1. Green colour if not otherwise stated
Marking	UNIKA (Italy) – Ethernet Cable CAT. 5e (4x2x24AWG/7)M - 100 ohm - WW/ YYYY – <i>traceability code</i>

Type: **1x4x20 AWG/19 SF/UTP**
Code: **RW100F** (for green outer jacket)
Code: **RW100G** (for blue outer jacket)



CONSTRUCTION	
Conductor	stranded tinned copper wire – 20 AWG/19 (0,50 mm²)
Insulation	polyolefin
Insulation colours	white ÷ blue ÷ yellow ÷ orange
Assembly of core	Stranded to quad: • pair 1 white/blue • pair 2 yellow/orange
Separation	polyester tape
Overall shield	aluminium/polyester tape + tinned copper braid 85% coverage
Outer jacket	crosslinked compound, type EM104 according to standard EN 50264-1. Green colour if not otherwise stated
Marking	UNIKA (Italy) – Profinet Cable CAT. 5e (1x4x20AWG/19)M - 100 ohm - WW/ YYYY – <i>traceability code</i>


Type: **1x4x24 AWG/7 SF/UTP**
Code: **RW100H**



CONSTRUCTION	
Conductor	stranded bare copper wire – 24 AWG/7
Insulation	Polyolefin
Insulation colours	white ÷ blue ÷ yellow ÷ orange
Assembly of core	Stranded to quad: • pair 1 white/blue • pair 2 yellow/orange
Separation	polyester tape
Inner jacket	Halogen-free compound
Overall shield	aluminium/polyester tape + tinned copper braid 85% coverage
Outer jacket	crosslinked compound, type EM104 according to standard EN 50264-1 - green colour if not otherwise stated
Marking	UNIKA (Italy) – Profinet Cable CAT. 5e (1x4x24 AWG/7) M - 100 ohm - WW/ YYYY – <i>traceability code</i>

Type: **2x2x22 AWG/19 SF/UTP**
Code: **RW100J**

UNIKA



CONSTRUCTION	
Conductor	stranded tinned copper wire – 22 AWG/19
Insulation	Polyolefin
Insulation colours	white ÷ blue ÷ yellow ÷ orange
Assembly of core	Stranded to quad: • pair 1 white/blue • pair 2 yellow/orange
Separation	polyester tape
Overall shield	aluminium/polyester tape + tinned copper wire braid
Outer jacket	crosslinked compound, type EM104 according to standard EN 50264-1 - green colour if not otherwise stated
Marking	UNIKA (Italy) – Ethernet Cable CAT. 5e (2x2x22 AWG/19) M - 100 ohm - WW/ YYYY – <i>traceability code</i>

	RW100A 1x4x22 AWG/19	RW100B 1x4x26 AWG/7	RW100C 4x2x22 AWG/19	RW100D 4x2x26 AWG/7	RW100E 4x2x24 AWG/7	RW100F RW100G 1x4x20 AWG/19	RW100H 1x4x24 AWG/7	RW100J 2x4x22 AWG/19
Max DC conductor resistance	60 Ω/km	145 Ω/km	60 Ω/km	170 Ω/km	88 Ω/km	36,4 Ω/km	88 Ω/km	60 Ω/km
Capacitance	55 pF/m	52 pF/m	54 pF/m	52 pF/m	52 pF/m	49 pF/m	50 pF/m	52 pF/m
Characteristic impedance (1÷100 MHz)	100 Ω (±15%)	100 Ω (±15%)	100 Ω (±15%)	100 Ω (±15%)	100 Ω (±15%)	100 Ω (±15%)	100 Ω (±15%)	100 Ω (±15%)
Voltage rating	300 V	300 V	300 V	300 V	300 V	300 V	300 V	300 V
Min insulation resistance	5,0 GΩx- km	5,0 GΩx- km	5,0 GΩx- km	5,0 GΩx- km	5,0 GΩx- km	5,0 GΩx- km	5,0 GΩx- km	5,0 GΩx- km
Nominal velocity of propagation 100MHz	67%	65%	78%	71%	77%	67%	67%	77%
Nominal attenuation 1 MHz	1,8 dB/100m	3,0 dB/100m	2,4 dB/100m	2,6 dB/100m	2,1 dB/100m	1,7 dB/100m	1,7 dB/100m	3,2 dB/100m
10 MHz	5,7 dB/100m	9,1 dB/100m	7,8 dB/100m	8,1 dB/100m	6,0 dB/100m	5,3 dB/100m	6,8 dB/100m	9,5 dB/100m
100 MHz	20,7 dB/100m	29,8 dB/100m	26,4 dB/100m	27,3 dB/100m	21,0 dB/100m	17,8 dB/100m	24,9 dB/100m	32 dB/100m
Nominal weight	63 kg/ km	40 kg/km	115 kg/km	60 kg/km	70 kg/km	110 kg/km	65 kg/km	80 kg/km
Nominal diameter	6,5 mm	4,8 mm	8,6 mm	6,5 mm	7,0 mm	8,6 mm	6,2 mm	8,0 mm
Minimum bending radius	8 x outer ø							
Temperature range	-40 °C +90°C							

Fire safety: cables are classified in compliance with the highest requirements established by hazard level HL3 into Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B).

The characteristics of the products, described in the data sheet, do not constitute any contractual binding.

UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.

TDS 00/2025

UNIKA - ROLLING STOCK CABLES - UNIRAIL D – ETHERNET CABLE CATEGORY 5e